

# Lever styles

## Standard levers



03  
Knurling available







06  
Default lever  
Knurling available






17  
Knurling available

Standard trim

	EO	DT	NL	NL-OP
				
<b>Product description</b>	22EO	22DT	22NL	22NL-OP
<b>Trim description</b>	—	210DT*	210NL*	110NL-MD* 110NL-WD*
<b>Escutcheon plate size</b>	—	5 <sup>3</sup> / <sub>8</sub> " x 4 <sup>25</sup> / <sub>32</sub> " x 3 <sup>3</sup> / <sub>32</sub> " (137 x 121 x 2 mm)	5 <sup>3</sup> / <sub>8</sub> " x 4 <sup>25</sup> / <sub>32</sub> " x 3 <sup>3</sup> / <sub>32</sub> " (137 x 121 x 2 mm)	—
<b>Pull center to center</b>	—	—	—	—
<b>Projection</b>	—	1 <sup>31</sup> / <sub>32</sub> " (42 mm)	1 <sup>31</sup> / <sub>32</sub> " (42 mm)	—
<b>ANSI function</b>	01	02	03	03
<b>Cylinder type</b>	—	—	Rim	Rim
<b>Handing</b>	—	—	—	—
<b>Optional trim</b>	230EO	230DT	230NL	—
<b>Optional #425 sex bolt quantity for device</b>	6 (with no trim) 2 (with EO trim)	2	2	6

\*ANSI/BHMA A156.3 (2001) Grade 1 trim

	TP	K	L
			
<b>Product description</b>	22TP	22K	22L
<b>Trim description</b>	230TP*	210K	230L*
<b>Escutcheon plate size</b>	3" x 12 <sup>1</sup> / <sub>16</sub> " x 3 <sup>3</sup> / <sub>32</sub> " (76 x 306 x 2 mm)	3" x 4 <sup>25</sup> / <sub>32</sub> " x 3 <sup>3</sup> / <sub>32</sub> " (76 x 121 x 2 mm)	3" x 6 <sup>3</sup> / <sub>8</sub> " x 1 <sup>5</sup> / <sub>16</sub> " (76 x 162 x 24 mm)
<b>Pull center to center</b>	5 <sup>1</sup> / <sub>2</sub> " (140 mm)	—	—
<b>Projection</b>	2" (51 mm)	2 <sup>15</sup> / <sub>16</sub> " (75 mm)	2 <sup>5</sup> / <sub>8</sub> " (67 mm)
<b>ANSI function</b>	05	08	08
<b>Cylinder type</b>	1 <sup>1</sup> / <sub>4</sub> " Mortise	Furnished	1 <sup>1</sup> / <sub>4</sub> " Mortise
<b>Handing</b>	—	—	—
<b>Optional trim</b>	230TP-BE	210K-BE	230L-BE
<b>Optional #425 sex bolt quantity for device</b>	2	2	2

\*ANSI/BHMA A156.3 (2008) Grade 1 trim

## 22 Optional trim

### 210 Series trim







The 210DT and 210NL have a heavy 10 gauge (2.4mm) stainless steel escutcheon. Rim Cylinder must be ordered separately for the 210NL trim. The 210K knob trim has a 10 gauge (2.4mm) steel escutcheon and uses the Schlage "A" orbit knob with six pin "C" keyway.

### 110NL Cylinder kit

Cylinder kit is available MD for metal doors or WD for wood doors. Metal door application supplied standard if door material is not specified. When ordering with device, specify function NL-OP. Rim Cylinder must be ordered separately.

### 230 Series trim

The 230EO, 230DT, 230NL and 230TP have a heavy 10 gauge (2.4mm) steel escutcheon. The 230L has a cast zinc  $\frac{3}{4}$ " (19mm) depth escutcheon. #06 lever style furnished standard, #03 and #17 optional style levers are available. 230L furnished RHR if handing is not specified. Cylinder must be ordered separately for the 230NL, 230TP and 230L trims.

	EO	DT	NL	TP-BE	L-BE	K-BE
						
	Exit only plate	Dummy trim pull when dogged	Night latch key retracts latch bolt	Thumbpiece blank escutcheon always operable, no cylinder	Lever blank escutcheon always operable, no cylinder	Knob blank escutcheon always operable, no cylinder
Trim description	230EO	230DT**	230NL**	230TP-BE**	230L-BE**	210K-BE
Escutcheon plate size	3" x 12 $\frac{1}{16}$ " x $\frac{3}{32}$ " (76 x 306 x 2 mm)	3" x 12 $\frac{1}{16}$ " x $\frac{3}{32}$ " (76 x 306 x 2 mm)	3" x 12 $\frac{1}{16}$ " x $\frac{3}{32}$ " (76 x 306 x 2 mm)	3" x 12 $\frac{1}{16}$ " x $\frac{3}{32}$ " (76 x 306 x 2 mm)	3" x 6 $\frac{3}{8}$ " x $\frac{15}{16}$ " (76 x 162 x 24 mm)	3" x 4 $\frac{25}{32}$ " x $\frac{3}{32}$ " (76 x 121 x 2 mm)
Pull center to center	—	5 $\frac{1}{2}$ " (140 mm)	5 $\frac{1}{2}$ " (140 mm)	5 $\frac{1}{2}$ " (140 mm)	—	—
Projection	—	2" (51 mm)	2" (51 mm)	2" (51 mm)	2 $\frac{3}{8}$ " (67 mm)	2 $\frac{15}{16}$ " (75 mm)
ANSI function	01	02	03	—	—	—
Cylinder type	—	—	Rim	—	—	—
*Optional #425 sex bolt quantity for device	2	2	6	—	2	2
*Additional 425 SNB for 499F strike	2	2	2	2	2	2

\*Sex Bolts are required for wood fire doors  
 \*\*ANSI/BHMA A156.3 (2008) Grade 1 Trim